Major Elements by

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Gold Reference Material Product Code

G901-2

Certified Control Values

50 gram Fire Assay

Gold Grade 1.76 ppm Standard Deviation 0.14 ppm Confidence Interval +/- 0.03 ppm

Aqua Regia Digest

Gold Grade 1.70 ppm Standard Deviation 0.13 ppm Confidence Interval +/- 0.036 ppm



Neutron Activation

CRM Details

Control Statistic Details

Control statistics were produced from results accumulated in the October-2001 round robin. A total of 88 fire assay results and 54 results from an aqua regia technique were used to certify this material.

Material Description

This material is described as an Oxide Ore Kalgoorlie.

Colour Designation (ISCC-NBS, SP440)

This material is grayish orange in colour.

Usage

This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.

Preparation and Packaging

All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.

Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.

Assay Testwork

All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.

Stability

This product remains stable in its original packaging, away from direct sunlight.

Material Safety

This product is not hazardous and non-toxic.

Analysis Results (ppm. Fusion / XRF (%) unless otherwise noted Fe Antimony 4 74 nr SiO₂ Arsenic nr Al₂O₃ Barium 1100 nr **Bromine** 20.2 TiO₂ nr Cadmium nr MnO nr Caesium 3.62 CaO nr Calcium (%) <1 Р nr Cerium 136 S nr Chromium 293 MgO nr Cobalt K₂O 21.8 nr Europium 2.25 Na₂O nr LOI1000 Gold (ppb) 1600 nr Hafnium 3.45 Neutron Activation Iridium (ppb) <20 Iron (%) Analyses and Fusion / 4.47 XRF Analyses are Lanthanum 75.1 Lutetium 0.24 single results and are indicative only. These Mercury nr are provided for matrix Molybdenum <5 Neodymium nr identification Nickel purposes. nr Potassium (%) 1.42 Rubidium 35.3 'nr': Not Reported Samarium 9.79 Scandium 12.5 Selenium <5 Silver <5 Sodium (%) 1.99 Strontium nr Tantalum <1 Tellurium <5 Terbium nr Thorium 148 Tin nr Tungsten 72.1 Uranium 3.61 Ytterbium 1.79 7inc 142 Zirconium <500

20 Hines Road, O'Connor, Western Australia 6163 Phone: +61 8 9314 2566, Fax: +61 8 9314 3699 e-mail: pjh@geostats.com.au, srr@geostats.com.au Website http://www.geostats.com.au