

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

GBM301-10

Certified Control Values



GBM301-10

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code:

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	534	50	63	+/- 12.6
Copper (ppm)	1226	89	73	+/- 20.8
Zinc (ppm)	2262	148	70	+/- 35.6
Lead (ppm)	610	53	69	+/- 12.8
Arsenic (ppm)	100060	5306	51	+/- 1507
Cobalt (ppm)	253	28	59	+/- 7.3
Silver (ppm)	6.5	1.6	64	+/- 0.4

CRM Details

<u>Control Statistic Details</u> Control statistics were produced from results accumulated in the April-2001 round robin. The number of results used to certify each analyte is shown in the table above.	<u>Neutron Activation Analysis Results (ppm, unless otherwise noted)</u>		<u>Major Elements by Fusion / XRF (%)</u>	
	<u>Material Description</u> This material is described as a Sulphide concentrate with arseno-pyrite.	Antimony	563	Fe
<u>Colour Designation (ISCC-NBS, SP440)</u> This material is grayish black in colour.	Arsenic	85700	SiO ₂	nr
<u>Usage</u> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.	Barium	<400	Al ₂ O ₃	nr
<u>Preparation and Packaging</u> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging. Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	Bromine	<5	TiO ₂	nr
<u>Assay Testwork</u> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.	Cadmium	nr	MnO	nr
<u>Stability</u> This product remains stable in its original packaging, away from direct sunlight.	Caesium	<3	CaO	nr
<u>Material Safety</u> This product is not hazardous and non-toxic.	Calcium (%)	<1	P	nr
	Cerium	204	S	nr
	Chromium	204	MgO	nr
	Cobalt	221	K ₂ O	nr
	Europium	3.94	Na ₂ O	nr
	Gold (ppb)	64800	LOI1000	nr
	Hafnium	<3		
	Iridium (ppb)	<60	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.	
	Iron (%)	21.8	'nr': Not Reported	
	Lanthanum	103		
	Lutetium	0.25		
	Mercury	nr		
	Molybdenum	<40		
	Neodymium	nr		
	Nickel	nr		
	Potassium (%)	<1		
	Rubidium	<20		
	Samarium	18		
	Scandium	10.6		
	Selenium	<20		
	Silver	<15		
	Sodium (%)	0.125		
	Strontium	nr		
	Tantalum	<1		
	Tellurium	<20		
	Terbium	nr		
	Thorium	25.3		
	Tin	nr		
	Tungsten	266		
	Uranium	<10		
	Ytterbium	2.01		
	Zinc	1580		
	Zirconium	<1000		

20 Hines Road, O'Connor, Western Australia 6163

Phone : +61 8 9314 2566, Fax : +61 8 9314 3699

e-mail : pjh@geostats.com.au, srr@geostats.com.au

Website <http://www.geostats.com.au>