


GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

GBM312-1

Certified Control Values



GBM312-1

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code:

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	8	4	142	+/- 0.7
Copper (ppm)	11	5	182	+/- 0.8
Zinc (ppm)	8	5	145	+/- 0.7
Lead (ppm)	17	6	160	+/- 0.9
Arsenic (ppm)	17	9	144	+/- 1.4
Cobalt (ppm)	2	2	72	+/- 0.4
Silver (ppm)	0.8	0.7	76	+/- 0.16

CRM Details

<u>Control Statistic Details</u> Control statistics were produced from results accumulated in the October-2012 round robin. The number of results used to certify each analyte is shown in the table above.	<u>Neutron Activation Analysis Results (ppm, unless otherwise noted)</u>		<u>Major Elements by Fusion / XRF (%)</u>	
	<u>Material Description</u> This material is described as a Laterite.	Antimony	3.02	Fe
<u>Colour Designation (ISCC-NBS, SP440)</u> This material is moderate reddish brown in colour.	Arsenic	24.25	SiO ₂	21.835
<u>Usage</u> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.	Barium	110	Al ₂ O ₃	34.155
<u>Preparation and Packaging</u> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging. Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	Bromine	4.57	TiO ₂	1.554
<u>Assay Testwork</u> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.	Cadmium	<5	MnO	0.045
<u>Stability</u> This product remains stable in its original packaging, away from direct sunlight.	Caesium	0.65	CaO	0.015
<u>Material Safety</u> This product is not hazardous and non-toxic.	Calcium (%)	nr	P	0.014
	Cerium	23.75	S	0.053
	Chromium	183.5	MgO	0.04
	Cobalt	2	K ₂ O	0.177
	Europium	0.1	Na ₂ O	0.031
	Gold (ppb)	<1	LOI1000	17.7
	Hafnium	14.3		
	Iridium (ppb)	<10		
	Iron (%)	16.6		
	Lanthanum	5.5		
	Lutetium	0.2		
	Mercury	nr		
	Molybdenum	23		
	Neodymium	nr		
	Nickel	8		
	Potassium (%)	nr		
	Rubidium	15.5		
	Samarium	0.75		
	Scandium	12.4		
	Selenium	<2		
	Silver	2		
	Sodium (%)	0.016		
	Strontium	nr		
	Tantalum	2.55		
	Tellurium	<10		
	Terbium	0.5		
	Thorium	87.5		
	Tin	<100		
	Tungsten	3		
	Uranium	6.8		
	Ytterbium	0.705		
	Zinc	10		
	Zirconium	440		

20 Hines Road, O'Connor, Western Australia 6163

Phone : +61 8 9314 2566, Fax : +61 8 9314 3699

e-mail : pjh@geostats.com.au, srr@geostats.com.au

Website <http://www.geostats.com.au>