

# GEOSTATS PTY LTD

Mining Industry Consultants  
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

## GBM319-10



Certified Control Values

### Total Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	6	2	51	+/- 0.5
Copper (ppm)	122	10	63	+/- 2.5
Zinc (ppm)	831	37	66	+/- 9.2
Lead (ppm)	75	7	58	+/- 1.8
Arsenic (ppm)	2196	124	58	+/- 33
Cobalt (ppm)	3	1	50	+/- 0.3
Silver (ppm)	1.1	0.2	47	+/- 0.05

### Partial Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	5	2	50	+/- 0.6
Copper (ppm)	116	9	71	+/- 2.2
Zinc (ppm)	804	47	64	+/- 11.9
Lead (ppm)	59	12	62	+/- 3.1
Arsenic (ppm)	2135	119	59	+/- 31.3
Cobalt (ppm)	3	1	40	+/- 0.4
Silver (ppm)	0.8	0.1	46	+/- 0.04

### CRM Details

<u>Control Statistic Details</u> Control statistics were produced from results accumulated in the April-2019 round robin. The number of results used to certify each analyte is shown in the table above.	<u>Neutron Activation Analysis Results (ppm, unless otherwise noted)</u>		<u>Major Elements by Fusion / XRF (%)</u>	
		Antimony	17.1	Fe
	Arsenic	2145	SiO <sub>2</sub>	56.07
	Barium	<100	Al <sub>2</sub> O <sub>3</sub>	9.23
	Bromine	<2	TiO <sub>2</sub>	0.58
	Cadmium	<10	MnO	0.08
	Caesium	2	CaO	0.09
	Calcium (%)	nr	P	0.059
	Cerium	22	S	0.13
	Chromium	<20	MgO	0.16
	Cobalt	3	K <sub>2</sub> O	1.36
	Europium	0.6	Na <sub>2</sub> O	0.19
	Gold (ppb)	94	LOH000	3.59
	Hafnium	<5	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.  'nr': Not Reported	
	Iridium (ppb)	<50		
	Iron (%)	18.8		
	Lanthanum	12		
	Lutetium	0.2		
	Mercury	nr		
	Molybdenum	<10		
	Neodymium	nr		
	Nickel	<20		
	Potassium (%)	nr		
	Rubidium	29		
	Samarium	1.9		
	Scandium	8.6		
	Selenium	12		
	Silver	<5		
	Sodium (%)	0.14		
	Strontium	nr		
	Tantalum	<2		
	Tellurium	<20		
	Terbium	<1		
	Thorium	3.3		
	Tin	<200		
	Tungsten	6		
	Uranium	<1		
	Ytterbium	1.2		
	Zinc	800		
	Zirconium	<500		
<u>Material Description</u> This material is described as an Oxidised coarse grained hydraulic breccia, Eastern Pilbara Western Australia.				
<u>Colour Designation (ISCC-NBS, SP440)</u> This material is moderate reddish brown in colour.				
<u>Usage</u> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.				
<u>Preparation and Packaging</u> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.  Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.				
<u>Assay Testwork</u> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.				
<u>Stability</u> This product remains stable in its original packaging, away from direct sunlight.				
<u>Material Safety</u> This product is not hazardous and non-toxic.				

20 Hines Road, O'Connor, Western Australia 6163  
Phone: +61 8 9314 2566 | Email: info@geostats.com.au  
Website: www.geostats.com.au

GBM319-10

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code: