

# GEOSTATS PTY LTD

Mining Industry Consultants  
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

## GBM321-4



### Certified Control Values

#### Total Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	39	2	51	+/- 0.6
Copper (ppm)	254	12	53	+/- 3.2
Zinc (ppm)	753	26	53	+/- 7.4
Lead (ppm)	29	3	49	+/- 0.8
Arsenic (ppm)	100	5	44	+/- 1.4
Cobalt (ppm)	21	1	47	+/- 0.3
Silver (ppm)	1.4	0.1	42	+/- 0.05

#### Partial Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	37	3	51	+/- 1
Copper (ppm)	253	12	70	+/- 2.9
Zinc (ppm)	736	31	54	+/- 8.6
Lead (ppm)	28	3	49	+/- 0.8
Arsenic (ppm)	93	11	52	+/- 3
Cobalt (ppm)	20	2	51	+/- 0.4
Silver (ppm)	1.3	0.2	55	+/- 0.05

### CRM Details

Control Statistic Details	Neutron Activation Analysis Results (ppm, unless otherwise noted)		Major Elements by Fusion / XRF (%)	
	Control statistics were produced from results accumulated in the April-2021 round robin. The number of results used to certify each analyte is shown in the table above.	Antimony	6.8	Fe
<b>Material Description</b> This material is described as a Fresh andesite, Pilbara, WA.	Arsenic	102	SiO <sub>2</sub>	59.56
	<b>Colour Designation (ISCC-NBS, SP440)</b> This material is very light gray in colour.	Barium	154	Al <sub>2</sub> O <sub>3</sub>
<b>Usage</b> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.		Bromine	<2	TiO <sub>2</sub>
	<b>Preparation and Packaging</b> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.  Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	Cadmium	<10	MnO
<b>Assay Testwork</b> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.		Caesium	5	CaO
	<b>Stability</b> This product remains stable in its original packaging, away from direct sunlight.	Calcium (%)	nr	P
<b>Material Safety</b> This product is not hazardous and non-toxic.		Cerium	46	S
	<b>Neutron Activation</b>	Chromium	63	MgO
<b>Fusion / XRF (%)</b>		Cobalt	22	K <sub>2</sub> O
	<b>Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.</b>	Europium	1	Na <sub>2</sub> O
<b>'nr': Not Reported</b>		Gold (ppb)	60	LOH1000
	<b>Neutron Activation</b>	Hafnium	<5	
<b>Fusion / XRF (%)</b>		Iridium (ppb)	<50	
	<b>Neutron Activation</b>	Iron (%)	6.1	
<b>Fusion / XRF (%)</b>		Lanthanum	23	
	<b>Neutron Activation</b>	Lutetium	0.3	
<b>Fusion / XRF (%)</b>		Mercury	nr	
	<b>Neutron Activation</b>	Molybdenum	<10	
<b>Fusion / XRF (%)</b>		Neodymium	nr	
	<b>Neutron Activation</b>	Nickel	40	
<b>Fusion / XRF (%)</b>		Potassium (%)	nr	
	<b>Neutron Activation</b>	Rubidium	81	
<b>Fusion / XRF (%)</b>		Samarium	4.1	
	<b>Neutron Activation</b>	Scandium	12.9	
<b>Fusion / XRF (%)</b>		Selenium	<10	
	<b>Neutron Activation</b>	Silver	<5	
<b>Fusion / XRF (%)</b>		Sodium (%)	0.27	
	<b>Neutron Activation</b>	Strontium	nr	
<b>Fusion / XRF (%)</b>		Tantalum	<2	
	<b>Neutron Activation</b>	Tellurium	<20	
<b>Fusion / XRF (%)</b>		Terbium	1	
	<b>Neutron Activation</b>	Thorium	4.68	
<b>Fusion / XRF (%)</b>		Tin	<200	
	<b>Neutron Activation</b>	Tungsten	5	
<b>Fusion / XRF (%)</b>		Uranium	<2	
	<b>Neutron Activation</b>	Ytterbium	2	
<b>Fusion / XRF (%)</b>		Zinc	770	
	<b>Neutron Activation</b>	Zirconium	<500	

20 Hines Road, O'Connor, Western Australia 6163

Phone: +61 8 9314 2566 | Email: info@geostats.com.au

Website: www.geostats.com.au

GBM321-4

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code: