


GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Ore Grade Base Metal Reference Material Product Code

GBM907-14

Certified Control Values



GBM907-14

Geostats Pty Ltd, Certified Ore Grade Base Metal Reference Material, Product Code:

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	42	6	78	+/- 1
Copper (ppm)	8126	378	185	+/- 55
Zinc (ppm)	31905	1340	166	+/- 206
Lead (ppm)	1947	99	165	+/- 15
Cobalt (ppm)	nr	nr	nr	nr
Silver (ppm)	8.5	0.7	110	+/- 0.13
Sulphur (%)	2.85	0.12	101	+/- 0.02

CRM Details

<u>Control Statistic Details</u> Control statistics were produced from results accumulated in the October-2007 & October-2018 round robins. The number of results used to certify each analyte is shown in the table above.	<u>Neutron Activation Analysis Results (ppm, unless otherwise noted)</u>		<u>Major Elements by Fusion / XRF (%)</u>	
	<u>Material Description</u> This material is described as a Low grade Copper / Zinc sulphide Ore.	Antimony	34.85	Fe
<u>Colour Designation (ISCC-NBS, SP440)</u> This material is light gray in colour.	Arsenic	198	SiO ₂	56.62
<u>Usage</u> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.	Barium	1765	Al ₂ O ₃	13.24
<u>Preparation and Packaging</u> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging. Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	Bromine	<1	TiO ₂	0.84
<u>Assay Testwork</u> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.	Cadmium	166.5	MnO	0.08
<u>Stability</u> This product remains stable in its original packaging, away from direct sunlight.	Caesium	0.9	CaO	3.52
<u>Material Safety</u> This product is not hazardous and non-toxic.	Calcium (%)	nr	P	0.107
	Cerium	164	S	2.9
	Chromium	37	MgO	1.91
	Cobalt	59.5	K ₂ O	3.37
	Europium	1.85	Na ₂ O	3.22
	Gold (ppb)	2795	LOI1000	3.27
	Hafnium	8	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.	
	Iridium (ppb)	<50	'nr': Not Reported	
	Iron (%)	5.25		
	Lanthanum	88		
	Lutetium	0.65		
	Mercury	nr		
	Molybdenum	24.5		
	Neodymium	nr		
	Nickel	51		
	Potassium (%)	nr		
	Rubidium	89		
	Samarium	11.35		
	Scandium	11.8		
	Selenium	<5		
	Silver	7.5		
	Sodium (%)	2.13		
	Strontium	nr		
	Tantalum	1.4		
	Tellurium	<10		
	Terbium	1.15		
	Thorium	29.5		
	Tin	<100		
	Tungsten	5		
	Uranium	4.65		
	Ytterbium	3.6		
	Zinc	32850		
	Zirconium	420		

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au