


# GEOSTATS PTY LTD

Mining Industry Consultants  
Reference Material Manufacture and Sales

Certified Geochem Base Metal Reference Material Product Code

## GBM915-5

Certified Control Values



GBM915-5

### Total Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	106	7	63	+/- 1.7
Copper (ppm)	307	19	69	+/- 4.5
Zinc (ppm)	333	20	67	+/- 4.8
Lead (ppm)	87	8	62	+/- 1.9
Arsenic (ppm)	128	7	44	+/- 2.2
Cobalt (ppm)	61	3	58	+/- 0.8
Silver (ppm)	3.9	0.4	56	+/- 0.1

### Partial Digest

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	91	7	57	+/- 1.9
Copper (ppm)	301	24	76	+/- 5.6
Zinc (ppm)	297	18	65	+/- 4.5
Lead (ppm)	85	10	62	+/- 2.7
Arsenic (ppm)	124	10	58	+/- 2.7
Cobalt (ppm)	48	5	59	+/- 1.4
Silver (ppm)	4.2	0.5	66	+/- 0.12

### CRM Details

Control Statistic Details	Neutron Activation Analysis Results (ppm, unless otherwise noted)	Major Elements by Fusion / XRF (%)	
<p>Control statistics were produced from results accumulated in the October-2015 round robin. The number of results used to certify each analyte is shown in the table above.</p> <p><b>Material Description</b> This material is described as a Cu Pb Zn Materials.</p> <p><b>Colour Designation (ISCC-NBS, SP440)</b> This material is light brownish gray in colour.</p> <p><b>Usage</b> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.</p> <p><b>Preparation and Packaging</b> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.</p> <p>Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.</p> <p><b>Assay Testwork</b> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.</p> <p><b>Stability</b> This product remains stable in its original packaging, away from direct sunlight.</p> <p><b>Material Safety</b> This product is not hazardous and non-toxic.</p>	<p>Antimony 6.32</p> <p>Arsenic 129</p> <p>Barium 210</p> <p>Bromine &lt;2</p> <p>Cadmium &lt;10</p> <p>Caesium 2</p> <p>Calcium (%) nr</p> <p>Cerium 31.9</p> <p>Chromium 85</p> <p>Cobalt 62</p> <p>Europium 1.57</p> <p>Gold (ppb) 2570</p> <p>Hafnium 5</p> <p>Iridium (ppb) &lt;50</p> <p>Iron (%) 9.6</p> <p>Lanthanum 16</p> <p>Lutetium 0.41</p> <p>Mercury nr</p> <p>Molybdenum &lt;10</p> <p>Neodymium nr</p> <p>Nickel 107</p> <p>Potassium (%) nr</p> <p>Rubidium 39</p> <p>Samarium 4.8</p> <p>Scandium 24.5</p> <p>Selenium &lt;10</p> <p>Silver &lt;5</p> <p>Sodium (%) 2.03</p> <p>Strontium nr</p> <p>Tantalum &lt;2</p> <p>Tellurium &lt;20</p> <p>Terbium 1</p> <p>Thorium 9.28</p> <p>Tin &lt;200</p> <p>Tungsten &lt;5</p> <p>Uranium 3</p> <p>Ytterbium 3</p> <p>Zinc 344</p> <p>Zirconium &lt;500</p>	<p>Fe 9.86</p> <p>SiO<sub>2</sub> 53.66</p> <p>Al<sub>2</sub>O<sub>3</sub> 13.61</p> <p>TiO<sub>2</sub> 1.76</p> <p>MnO 0.16</p> <p>CaO 6.71</p> <p>P 0.078</p> <p>S 0.124</p> <p>MgO 3.59</p> <p>K<sub>2</sub>O 1.06</p> <p>Na<sub>2</sub>O nr</p> <p>LOI1000 1.09</p>	<p>Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.</p> <p>'nr': Not Reported</p>

20 Hines Road, O'Connor, Western Australia 6163  
Phone : +61 8 9314 2566, Fax : +61 8 9314 3699  
e-mail : [pjh@geostats.com.au](mailto:pjh@geostats.com.au), [srr@geostats.com.au](mailto:srr@geostats.com.au)  
Website <http://www.geostats.com.au>

Geostats Pty Ltd, Certified Geochem Base Metal Reference Material, Product Code: