

# GEOSTATS PTY LTD

Mining Industry Consultants  
Reference Material Manufacture and Sales

## Certified Low Level Gold Reference Material Product Code

# GLG305-5

## Certified Control Values

### Low Level Gold

Gold Grade	82.24 ppb
Standard Deviation	13.22 ppb
Confidence Interval	+/- 4.17 ppb



## CRM Details

<u>Control Statistic Details</u>	<u>Neutron Activation Analysis Results (ppm, unless otherwise noted)</u>		<u>Major Elements by Fusion / XRF (%)</u>	
	Control statistics were produced from results accumulated in the April-2005 round robin. A total of 42 gold assays were used to certify this material.	Antimony	1.15	Fe
<u>Material Description</u> This material is described as an Eastern Goldfields blended Laterite and Oxide.	Arsenic	21.2	SiO <sub>2</sub>	nr
	Barium	153	Al <sub>2</sub> O <sub>3</sub>	nr
<u>Colour Designation (ISCC-NBS, SP440)</u> This material is moderate orange pink in colour.	Bromine	1.1	TiO <sub>2</sub>	nr
	Cadmium	<3.2	MnO	nr
<u>Usage</u> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.	Caesium	1.31	CaO	nr
	Calcium (%)	nr	P	nr
<u>Preparation and Packaging</u> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.  Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	Cerium	12.1	S	nr
	Chromium	74.9	MgO	nr
<u>Assay Testwork</u> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.	Cobalt	7.58	K <sub>2</sub> O	nr
	Europium	0.21	Na <sub>2</sub> O	nr
<u>Stability</u> This product remains stable in its original packaging, away from direct sunlight.	Gold (ppb)	88	LOI1000	nr
	Hafnium	3.84	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.	
<u>Material Safety</u> This product is not hazardous and non-toxic.	Iridium (ppb)	3.4	'nr': Not Reported	
	Iron (%)	2.93		
	Lanthanum	5.27		
	Lutetium	0.403		
	Mercury	<0.09		
	Molybdenum	1.5		
	Neodymium	3.65		
	Nickel	<32		
	Potassium (%)	3.31		
	Rubidium	327		
	Samarium	1.26		
	Scandium	6.1		
	Selenium	<0.86		
	Silver	<0.66		
	Sodium (%)	1.55		
	Strontium	nr		
	Tantalum	2.34		
	Tellurium	<2.7		
	Terbium	0.38		
	Thorium	8.57		
	Tin	<36		
	Tungsten	<0.93		
	Uranium	2.51		
	Ytterbium	2.63		
	Zinc	15		
	Zirconium	150		

20 Hines Road, O'Connor, Western Australia 6163

Phone : +61 8 9314 2566, Fax : +61 8 9314 3699

e-mail : pjh@geostats.com.au, srr@geostats.com.au

Website <http://www.geostats.com.au>

GLG305-5

Geostats Pty Ltd, Certified Low Level Gold Reference Material, Product Code: