Major Elements by

# **GEOSTATS PTY LTD**

Mining Industry Consultants
Reference Material Manufacture and Sales

### **Certified Low Level Gold Reference Material Product Code**

**GLG323-3** 

# **Certified Control Values**

## **Low Level Gold**

Gold Grade 84.99 ppb

Standard Deviation 8.82 ppb

Confidence Interval +/- 1.38 ppb



**Neutron Activation** 

### **CRM Details**

#### Fusion / XRF (%) Control Statistic Details Analysis Results (ppm, Control statistics were produced from results accumulated in the April-2023, unless otherwise noted) October-2013 round robins. A total of 161 gold assays were used to certify this Antimony 3 59 13 SiO<sub>2</sub> material. Arsenic 365 68.15 Barium 522 Al<sub>2</sub>O<sub>3</sub> 13.16 Material Description Bromine TiO<sub>2</sub> <2 0.711 This material is described as an Oxide milled mine waste. Cadmium <10 MnO 0.07 Caesium CaO 3 39 4 Calcium (%) nr 0.041 s Colour Designation (ISCC-NBS, SP440) Cerium 51 0.1 Chromium This material is pale red in colour. 49 MgO 1.66 Cobalt 2.96 354 K<sub>2</sub>O <u>Usage</u> Europium Na<sub>2</sub>O 3.397 1 This product is for use in the mining industry as a reference material for Gold (ppb) 85 LOI1000 0.58 monitoring and testing the accuracy of laboratory assaying. Hafnium <5 Iridium (ppb) <50 **Neutron Activation** Preparation and Packaging Iron (%) 3.6 Analyses and Fusion / Lanthanum All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry 28 XRF Analyses are material is then pulverised to better than 75 micron (nominal mean of 45 micron) Lutetium 0.3 single results and are using an air classifier. The material is then homogenised and stored in a sealed, Mercury nr indicative only. These stable container ready for final packaging. Molybdenum 26 are provided for matrix Neodymium nr Materials are statistically sampled from stores, then packaged into either heat Nickel 201 identification purposes. sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready Potassium (%) nr for distribution. All packaging has been chosen to ensure minimal contamination Rubidium 130 'nr': Not Reported from outside sources during shipment, use and storage. Samarium 4.5 Scandium 10.6 Assay Testwork Selenium <10 All standards are tested thoroughly in the Geostats bi-annual laboratory survey. Silver <5 Sodium (%) This involves assaying by multiple laboratories from around the world. Results 2.35 are compiled into a comprehensive report detailing statistics for each standard. Strontium nr Assay distributions are checked and processed statistically, producing Tantalum <2 monitoring statistics for these standards. Materials are tested regularly to ensure Tellurium <20 stability and homogeneity. Terbium <1 Thorium 21.4

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au

This product remains stable in its original packaging, away from direct sunlight.

Tin

Zinc Zirconium

Tungsten

Uranium

Ytterbium

<200

2

10

2.4

326

<500

**Stability** 

Material Safety

This product is not hazardous and non-toxic.