

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales


Certified Low Level Gold Reference Material Product Code

GLG913-4

Certified Control Values

Low Level Gold

Gold Grade 3.10 ppb
Standard Deviation 1.67 ppb
Confidence Interval +/- 0.36 ppb



CRM Details

<u>Control Statistic Details</u>	<u>Neutron Activation Analysis Results (ppm, unless otherwise noted)</u>		<u>Major Elements by Fusion / XRF (%)</u>	
	Control statistics were produced from results accumulated in the October-2013 & April-2015 round robins. A total of 88 gold assays were used to certify this material.	Antimony	0.192	Fe
<u>Material Description</u> This material is described as a Basalt.	Arsenic	1.655	SiO ₂	74.59
	Barium	2445	Al ₂ O ₃	10.695
<u>Colour Designation (ISCC-NBS, SP440)</u> This material is very light gray in colour.	Bromine	0.577	TiO ₂	0.405
	Cadmium	<5	MnO	0.06
<u>Usage</u> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.	Caesium	0.855	CaO	1.325
	Calcium (%)	nr	P	0.08
<u>Preparation and Packaging</u> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging. Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.	Cerium	169.5	S	0.189
	Chromium	22.6	MgO	0.96
<u>Assay Testwork</u> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.	Cobalt	9.755	K ₂ O	4.65
	Europium	1.9	Na ₂ O	1.535
<u>Stability</u> This product remains stable in its original packaging, away from direct sunlight.	Gold (ppb)	1.7	LOI1000	0.89
	Hafnium	6.495	Neutron Activation Analyses and Fusion / XRF Analyses are single results and are indicative only. These are provided for matrix identification purposes.	
<u>Material Safety</u> This product is not hazardous and non-toxic.	Iridium (ppb)	<50	'nr': Not Reported	
	Iron (%)	3.22		
	Lanthanum	95.3		
	Lutetium	0.331		
	Mercury	nr		
	Molybdenum	5.295		
	Neodymium	nr		
	Nickel	<20		
	Potassium (%)	nr		
	Rubidium	118		
	Samarium	9.855		
	Scandium	4.98		
	Selenium	<10		
	Silver	<1		
	Sodium (%)	1.165		
	Strontium	nr		
	Tantalum	0.553		
	Tellurium	nr		
	Terbium	1.115		
	Thorium	24.8		
	Tin	nr		
	Tungsten	5.42		
	Uranium	2.46		
	Ytterbium	2		
	Zinc	52.8		
	Zirconium	nr		

20 Hines Road, O'Connor, Western Australia 6163

Phone : +61 8 9314 2566, Fax : +61 8 9314 3699

e-mail : pjh@geostats.com.au, srr@geostats.com.au

Website <http://www.geostats.com.au>

GLG913-4

Geostats Pty Ltd, Certified Low Level Gold Reference Material, Product Code: