Major Elements by

GEOSTATS PTY LTD

Mining Industry Consultants
Reference Material Manufacture and Sales

Certified Low Level Gold Reference Material Product Code

GLG921-1

Certified Control Values

Low Level Gold

Gold Grade 4.65 ppb

Standard Deviation 2.65 ppb

Confidence Interval +/- 0.69 ppb

Control Statistic Details

This product is not hazardous and non-toxic.



Neutron Activation

Analysis Results (ppm, Fusion / XRF (%)

CRM Details

	r many one recounts (pp.m.)			(,,,,
Control statistics were produced from results accumulated in the October-2021	unless otherwise noted)			
round robin. A total of 61 gold assays were used to certify this material.	Antimony	8.6	Fe	3.9
	Arsenic	104	SiO ₂	59.29
	Barium	252	Al ₂ O ₃	14.14
Material Description	Bromine	<2	TiO ₂	0.62
This material is described as a Fresh rhyolite, Pilbara, WA.	Cadmium	<10	MnO	0.59
	Caesium	8	CaO	4.02
	Calcium (%)	nr	Р	0.054
Colour Designation (ISCC-NBS, SP440)	Cerium	35	S	1.59
This material is very light gray in colour.	Chromium	81	MgO	2.02
	Cobalt	19	K ₂ O	3.2
<u>Usage</u>	Europium	0.8	Na ₂ O	0.39
This product is for use in the mining industry as a reference material for	Gold (ppb)	<5	LOI1000	7.85
monitoring and testing the accuracy of laboratory assaying.	Hafnium	<5		
	Iridium (ppb)	<50	Neutron Act	ivation
Preparation and Packaging	Iron (%)	4	Analyses ar	nd Fusion /
All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry	Lanthanum	19	XRF Analyses are	
material is then pulverised to better than 75 micron (nominal mean of 45 micron)	Lutetium	0.2	single results and are	
using an air classifier. The material is then homogenised and stored in a sealed,	Mercury	nr	- C	
stable container ready for final packaging.	Molybdenum	<10	indicative only. These	
	Neodymium	nr	are provided for matrix	
Materials are statistically sampled from stores, then packaged into either heat	Nickel	46	identification purposes.	
sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready	Potassium (%)	nr		
for distribution. All packaging has been chosen to ensure minimal contamination	Rubidium	102	'nr': Not Reported	
from outside sources during shipment, use and storage.	Samarium	3.1		
	Scandium	11.3		
Assay Testwork	Selenium	<10		
All standards are tested thoroughly in the Geostats bi-annual laboratory survey.	Silver	<5		
This involves assaying by multiple laboratories from around the world. Results	Sodium (%)	0.292		
are compiled into a comprehensive report detailing statistics for each standard.	Strontium	nr		
Assay distributions are checked and processed statistically, producing	Tantalum	<2		
monitoring statistics for these standards. Materials are tested regularly to ensure	Tellurium	<20		
stability and homogeneity.	Terbium	<1		
	Thorium	5		
<u>Stability</u>	Tin	<200		
This product remains stable in its original packaging, away from direct sunlight.	Tungsten	2		
	Uranium	1		
Material Safety	Ytterbium	1.6		
1	17	= 4.0	1	

20 Hines Road, O'Connor, Western Australia 6163
Phone: +61 8 9314 2566 | Email: info@geostats.com.au
Website: www.geostats.com.au

Zinc

Zirconium

510

<500