


# GEOSTATS PTY LTD

Mining Industry Consultants  
Reference Material Manufacture and Sales

Certified Ore Grade Base Metal Reference Material Product Code

## GBM925-12

Certified Control Values



GBM925-12

Element	Grade	Standard Deviation	Num of Analyses	Confidence Interval
Nickel (ppm)	12706	659	261	+/- 80
Copper (ppm)	55	10	173	+/- 1
Zinc (ppm)	236	32	206	+/- 4
Lead (ppm)	13	10	89	+/- 2
Cobalt (ppm)	nr	nr	nr	nr
Silver (ppm)	1.1	0.9	104	+/- 0.18
Sulphur (%)	0.10	0.02	255	+/- 0

### CRM Details

<u>Control Statistic Details</u>	<u>Neutron Activation Analysis Results (ppm, unless otherwise noted)</u>	<u>Major Elements by Fusion / XRF (%)</u>	
Control statistics were produced from results accumulated in the October-2025, April-2016, April-2023 round robins. The number of results used to certify each analyte is shown in the table above.	Antimony <0.2	Fe	19.73
	Arsenic 3	SiO <sub>2</sub>	43.4
	Barium <100	Al <sub>2</sub> O <sub>3</sub>	5.34
	Bromine 10	TiO <sub>2</sub>	0.006
	Cadmium <10	MnO	0.249
	Caesium 2	CaO	0.19
	Calcium (%) nr	P	0.463
	Cerium 13	S	0.109
	Chromium 6910	MgO	10.2
	Cobalt 682	K <sub>2</sub> O	0.07
	Europium 1	Na <sub>2</sub> O	0.422
	Gold (ppb) <5	LOI1000	9.49
	Hafnium <5	Neutron Activation	
	Iridium (ppb) <50	Analyses and Fusion /	
	Iron (%) 20.2	XRF Analyses are	
	Lanthanum 11	single results and are	
	Lutetium 0.2	indicative only. These	
	Mercury nr	are provided for matrix	
	Molybdenum <10	identification	
	Neodymium nr	purposes.	
	Nickel 12900	'nr': Not Reported	
	Potassium (%) nr		
	Rubidium <20		
	Samarium 2.8		
	Scandium 27.9		
	Selenium <10		
	Silver <5		
	Sodium (%) 0.285		
	Strontium nr		
	Tantalum <2		
	Tellurium <20		
	Terbium 1		
	Thorium 0.7		
	Tin <200		
	Tungsten <2		
	Uranium <1		
	Ytterbium 1.2		
	Zinc 250		
	Zirconium <500		
<u>Material Description</u> This material is described as a Nickel laterite.			
<u>Colour Designation (ISCC-NBS, SP440)</u> This material is pale yellowish brown in colour.			
<u>Usage</u> This product is for use in the mining industry as a reference material for monitoring and testing the accuracy of laboratory assaying.			
<u>Preparation and Packaging</u> All CRMs are dried in an oven for a minimum of 12 hours at 110°C. The dry material is then pulverised to better than 75 micron (nominal mean of 45 micron) using an air classifier. The material is then homogenised and stored in a sealed, stable container ready for final packaging.  Materials are statistically sampled from stores, then packaged into either heat sealed, air tight, plastic pulp packets or screw top sealed plastic containers ready for distribution. All packaging has been chosen to ensure minimal contamination from outside sources during shipment, use and storage.			
<u>Assay Testwork</u> All standards are tested thoroughly in the Geostats bi-annual laboratory survey. This involves assaying by multiple laboratories from around the world. Results are compiled into a comprehensive report detailing statistics for each standard. Assay distributions are checked and processed statistically, producing monitoring statistics for these standards. Materials are tested regularly to ensure stability and homogeneity.			
<u>Stability</u> This product remains stable in its original packaging, away from direct sunlight.			
<u>Material Safety</u> This product is not hazardous and non-toxic.			

20 Hines Road, O'Connor, Western Australia 6163

Phone: +61 8 9314 2566 | Email: info@geostats.com.au

Website: www.geostats.com.au

Geostats Pty Ltd, Certified Ore Grade Base Metal Reference Material, Product Code: